



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/002,861	11/15/2001	Takao Sugawara	1990.65985	4780

7590 01/09/2006

Patrick G. Burns, Esq.
GREER, BURNS & CRAIN, LTD.
Suite 2500
300 South Wacker Dr.
Chicago, IL 60606

EXAMINER

RODRIGUEZ, GLENDA P

ART UNIT	PAPER NUMBER
----------	--------------

2651

DATE MAILED: 01/09/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 10/002,861	Applicant(s) SUGAWARA ET AL.	
	Examiner Glenda P. Rodriguez	Art Unit 2651	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
 - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
 - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 30 September 2005.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-14 and 18-23 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☒ Claim(s) 6, 13 and 23 is/are allowed.
- 6) ☒ Claim(s) 1-5, 7-12, 14 and 18-22 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1-5, 7-12, 14, 18-22 and 24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Mizokami et al. (US Patent No. 5, 523, 991) in view of Okazaki (US Patent No. 5, 838, 512).

Regarding Claim 1, 8 and 18, Mizokami et al. teaches an information recording and reproducing apparatus for recording and reproducing information onto/from a magnetic recording medium, comprising:

A data recording unit which inserts a predetermined specific code train into at least one or more portions of user data and records the data onto the medium upon data recording (Col. 2, L. 38-50 and Col. 11, L. 3-14);

And a data reproducing unit, which separates a head reproducing signal by using clocks and thereafter on the basis of phase information of two or more known revise bytes positioned on both sides of data phase errors of signal points of data existing among the points of data are estimated. thereby correcting the amplitude into an amplitude value of an original timing signal point. (Col. 11, L. 15-37. Wherein it teaches the code trains utilizing RLL encoding to synchronize the data. And See also Fig. 5A along with its description, wherein it illustrates a data area

20 along with two synchronization areas 2B, wherein resynchronism and phase and amplitude adjustments can be performed.).

Mizokami et al. does not explicitly teach wherein the code train is amplitude corrected. However, this feature is well known in the art as disclosed by Okazaki, wherein it teaches a variable gain amplifier to control the code trains (Col. 6, L. 14-24 and Col. 7, L. 10 of Okazaki, wherein it teaches that servo data is a code of train (another expression for code train) wherein this code is used for amplitude and synchronization purposes by using phase acquisition by a PLL circuit (See Abstract and Col. 3, L. 36-52. Okazaki further teaches a VGA, which is used for amplitude correction upon acquired data in Col. 1, L. 25-30. This read on the Applicant's description of amplitude correction according to the Applicant's Specification in Page 3, L. 12-24). It would have been obvious to a person of ordinary skill in the art, at the time the invention was made, to modify Mizokami et al.'s invention with the teaching of Okazaki in order to perform phase acquisition from the apparatus (See Abstract of Okazaki).

Regarding Claim 2, 9 and 19, Mizokami et al. teaches an information recording and reproducing apparatus for recording and reproducing information onto/from a magnetic recording medium, comprising:

A data recording unit which inserts a predetermined specific code train into at least one or more portions of user data and records the data onto the medium upon data recording (Col. 2, L. 38-50 and Col. 11, L. 3-14 of Mizokami et al);

And a data reproducing unit, which separates a head reproducing signal having an amplitude by using clocks and thereafter, on the basis of phase information of two or more known revise bytes positioned on both sides of data. phase errors of

signal points of data existing among the points of data are estimated. thereby correcting the amplitude into an amplitude value of an original timing signal point, (Col. 11, L. 15-37 of Mizokami et al. Wherein it teaches the code trains utilizing RLL encoding to synchronize the data. And See also Fig. 5A along with its description, wherein it illustrates a data area 20 along with two synchronization areas 2B, wherein resynchronize and phase and amplitude adjustments can be performed.).

Wherein said data recording unit and said data reproducing record and, thereafter, reproduce user data onto/from medium without encoding it to an RLL code (Col. 2, L. 33-37, Col.12, L.60-64 and Col. 15, L. 47-55 of Mizokami et al.).

Mizokami et al. does not explicitly teach wherein the code train is amplitude corrected. However, this feature is well known in the art as disclosed by Okazaki, wherein it teaches a variable gain amplifier to control the code trains (Col. 6, L. 14-24 and Col. 7, L. 10 of Okazaki, wherein it teaches that servo data is a code of train (another expression for code train) wherein this code is used for amplitude and synchronization purposes by using phase acquisition by a PLL circuit (See Abstract and Col. 3, L. 36-52. Okazaki further teaches a VGA, which is used for amplitude correction upon acquired data in Col. 1, L. 25-30. This read on the Applicant's description of amplitude correction according to the Applicant's Specification in Page 3, L. 12-24). It would have been obvious to a person of ordinary skill in the art, at the time the invention was made, to modify Mizokami et al.'s invention with the teaching of Okazaki in order to perform phase acquisition from the apparatus (See Abstract of Okazaki).

Art Unit: 2651

Regarding Claims 4, 11 and 21, Mizokami et al. teaches an information recording and reproducing apparatus for recording and reproducing information onto/from a magnetic recording medium, comprising:

A data recording unit which inserts a predetermined specific code train into at least one or more portions of user data and records the data onto the medium upon data recording (Col. 2, L. 38-50 and Col. 11, L. 3-14 of Mizokami et al);

And a data reproducing unit, which separates a head reproducing signal having an amplitude by using clocks and thereafter, ' on the basis of phase information of two or more known revise bytes positioned on both sides of data. phase errors of signal points of data existing among the points of data are estimated. thereby correcting the amplitude into an amplitude value of an original timing signal point, (Col. 11, L. 15-37 of Mizokami et al. Wherein it teaches the code trains utilizing RLL encoding to synchronize the data. And See also Fig. 5A along with its description, wherein it illustrates a data area 20 along with two synchronization areas 2B, wherein resynchronize and phase and amplitude adjustments can be performed.).

Wherein said data recording unit arranges sync bytes to the head position of each data which was split by said specific code train and records the data onto the medium, and said data reproducing unit detects sync bytes subsequent to said specific code train, presumes a head bit of the data, and obtains a synchronization of a decoding (Col. 17, L. 32-46, wherein it teaches it demonstrates a first sync

pattern being recorded (added) after the head of the coded data (It is very well known in the art that positional information is written at the head of a track.)).

Mizokami et al. does not explicitly teach wherein the code train is amplitude corrected. However, this feature is well known in the art as disclosed by Okazaki, wherein it teaches a variable gain amplifier to control the code trains (Col. 6, L. 14-24 and Col. 7, L. 10 of Okazaki, wherein it teaches that servo data is a code of train (another expression for code train) wherein this code is used for amplitude and synchronization purposes by using phase acquisition by a PLL circuit (See Abstract and Col. 3, L. 36-52. Okazaki further teaches a VGA, which is used for amplitude correction upon acquired data in Col. 1, L. 25-30. This read on the Applicant's description of amplitude correction according to the Applicant's Specification in Page 3, L. 12-24). It would have been obvious to a person of ordinary skill in the art, at the time the invention was made, to modify Mizokami et al.'s invention with the teaching of Okazaki in order to perform phase acquisition from the apparatus (See Abstract of Okazaki).

Regarding Claims 5, 8 and 22, Mizokami et al. and Okazaki teach all the limitations of Claims 1, 8 and 18, respectively. Mizokami further teach wherein said data recording unit arranges sync bytes to the head position of each data which was split by said specific code train and records the data onto the medium, and said data reproducing unit detects sync bytes subsequent to said specific code train, presumes a head bit of the data, and obtains a synchronization of a decoding (Col. 17, L. 32-46, wherein it teaches it demonstrates a first sync pattern being recorded (added) after the head of the coded data (It is very well known in the art that positional information is written at the head of a track.)).

Regarding Claims 7 and 14, Mizokami et al. teaches an information recording and reproducing apparatus for recording and reproducing information onto/from a magnetic recording medium, comprising:

A data recording unit which inserts a predetermined specific code train into at least one or more portions of user data and records the data onto the medium upon data recording (Col. 2, L. 38-50 and Col. 11, L. 3-14);

And a data reproducing unit, which separates a head reproducing signal by using clocks and thereafter, executes a clock extraction and an amplitude by using a signal corresponding to said specific code train upon data reproduction (Col. 11, L. 15-37. Wherein it teaches the code trains utilizing RLL encoding to synchronize the data.).

Mizokami et al. does not explicitly teach wherein the code train is amplitude corrected and Wherein said recording unit and said data reproducing unit are constructed by a signal processing integrated circuit and said signal processing integrated circuit is installed in a magnetic disk apparatus or an optical disk apparatus. However, this feature is well known in the art as disclosed by Okazaki, wherein it teaches a variable gain amplifier to control the code trains (Col. 6, L. 14-24 and Col. 7, L. 10 of Okazaki, wherein it teaches that servo data is a code of train (another expression for code train) wherein this code is used for amplitude and synchronization purposes by using phase acquisition by a PLL circuit (See Abstract and Col. 3, L. 36-52. Okazaki further teaches a VGA, which is used for amplitude correction upon acquired data in Col. 1, L. 25-30. This read on the Applicant's description of amplitude correction according to the Applicant's Specification in Page 3, L. 12-24) and Wherein

Art Unit: 2651

recording/reproducing unit are constructed by a signal processing integrated circuit and said signal processing integrated circuit is installed in a magnetic disk apparatus or an optical disk apparatus (Col. 5, L. 1-3 of Okazaki and also see Fig. 2). It would have been obvious to a person of ordinary skill in the art, at the time the invention was made, to modify Mizokami et al.'s invention with the teaching of Okazaki in order to perform phase acquisition from the apparatus (See Abstract of Okazaki).

Regarding Claims 3, 10 and 20, the combination of Mizokami et al. teach all the limitations of Claims 1, 8 and 18, respectively. Okazaki further teach wherein in the clock in the clock extraction by said data reproducing unit, an inherent sampling time is obtained on the basis of phase information extracted from the signal corresponding to said specific code train, and the signal amplitude synchronized with the clock is sampled again by an interpolating operation of an interpolating filter according to said sampling time (Col. 3, L. 36-54).

Allowable Subject Matter

3. Claims 6, 13, and 23 are allowed.

The reasons for allowance for these claims are in the Office Action dated on 5/06/2004.

Response to Arguments

4. Applicant's arguments with respect to claims 1-14 and 18-23 have been considered but are moot in view of the new ground(s) of rejection due to the newly amended Claims.

5. Examiner acknowledges that Claims 15-17 and 24 have been cancelled in the Amendment presented on 9/30/2005.

Conclusion

Art Unit: 2651

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Glenda P. Rodriguez whose telephone number is (571) 272-7561. The examiner can normally be reached on Monday thru Thursday: 7:00-5:00; alternate Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Hudspeth can be reached on (571) 272-7843. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).


gpr
01/03/06.


DAVID HUDSPETH
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600